



**SLADE Packing complies with the following MIL Specs:**

**MIL-P-24583B (SH)  
22 August 1991,**

**SUPERSEDING**

**MIL-P-24583A (SH)  
6 April 1990**

**PACKING MATERIAL, GRAPHITIC OR CARBON BRAIDED YARN**

<b>TYPE I</b>	Continuous filament graphitic yarn.... <b>Slade Style 3300G</b>
<b>TYPE II</b>	Staple Graphitic yarn (yarns fabricated using fibers having greater length than than 2 inches).... <b>Slade Style 3300G</b>
<b>Class 1</b>	For use where detrimental material and lubricant content of the packing need not be controlled beyond normal manufacturing limits ... <b>Slade Style 3300G</b>
<b>Class 2</b>	For use where detrimental material content must be controlled to limits specified in MIL-P-24583B (SH) ... <b>Slade Style 3300LC (FORMULATED FOR NUCLEAR SERVICES) Certifications provided.</b>
<b>Class 3</b>	For use where detrimental material content need not be controlled beyond normal manufacturing limits, and stuffing box temperatures do not exceed 250°C / 500°F Coated with PTFE.... <b>Slade Style 3300GTFE</b>
<b>Grade I</b>	Treated with corrosion inhibitor.... <b>Slade Style 3300LCI (Class 2) &amp; 3300GI (Class 1)</b>
<b>Grade N</b>	No Corrosion inhibitor .. <b>Slade Style 3300G (Class 1) and Slade Style 3300LC (Class 2)</b>

Available from:

**The DELAMAR Company  
www.delamar.net  
434-983-6104**